

PHARMACEUTICAL APPLICATION



Petri Dish Tray Feeding System

A custom material handling system for automated feeding of Petri Dishes from tray to processing

The Petri Dish Tray Feeding System was designed to feed plates into an automated processing system as an alternative to the existing loading system provided by the equipment manufacturer.

Incubating Trays are placed onto the input so that the Operator pushes the entire tray into the system and moves on to other tasks in the lab. Plates are transferred 90° toward the processing system and fed onto the system conveyor for downstream processing.

Turnkey controls interfaces with the processing system for balanced feed control.







automation · redefined

System Details

Mechanical Features: Stainless steel welded frame construction UHMW wear strips 400 series stainless steel bearings Tool-less tip-up pulley for cleaning Leveling feet and casters for portability Control Features: 115VAC 50/60 Hz operation Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Features: Stainless steel welded frame construction UHMW wear strips 400 series stainless steel bearings Tool-less tip-up pulley for cleaning Leveling feet and casters for portability Control Features: 115VAC 50/60 Hz operation Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control	Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds		
Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Features: • Stainless steel welded frame construction • UHMW wear strips • 400 series stainless steel bearings • Tool-less tip-up pulley for cleaning • Leveling feet and casters for portability Control Features: • 115VAC 50/60 Hz operation • Integrated safety circuit with E-Stop • Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds		
Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	 Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds 		 Stainless steel welded frame construction UHMW wear strips 400 series stainless steel bearings Tool-less tip-up pulley for cleaning
Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds	 Integrated safety circuit with E-Stop Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds 	Operational Experiences	• 115VAC 50/60 Hz operation
 Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds 	 Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds 	 Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds 	 Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds 	 Sensor-based interfacing with mating systems for conveyor control Cycle Time: 3 seconds 	Control Features:	
Cycle Time: 3 seconds	Cycle Time: 3 seconds	Cycle Time: 3 seconds	Cycle Time: 3 seconds	Cycle Time: 3 seconds		Sensor-based interfacing with mating systems for
Location: USA	Location: USA	Location: USA	Location: USA	Location: USA	Cycle Time:	3 seconds
	Location.	Location.	Location. Solv		Location:	USA